


PARAFUSO CABEÇA CHATA COM SEXTAVADO INTERNO

Métrico · DIN 7991 (* ISO 10642)



| Ø Nominal | M3 | M4 | M5 | M6 | M8 | M10 | M12 | M16 | M20 | M24 |
|------------------------|-------------|-------------|--------------|--------------|--------------|--------------|---------------|---------------|-------|-------|
| Chave s | 2 | 2.5 | 3 | 4 | 5 | 6 | 8 | 10 | 12 | 14 |
| Altura Cab. K | 1,7 (*1,86) | 2,3 (*2,48) | 2,8 (*3,10) | 3,3 (*3,72) | 4,4 (*4,96) | 5,5 (*6,20) | 6,5 (*7,44) | 7,5 (*8,80) | 8.50 | 14.00 |
| Ø da Cabeça dk | 6,0 (*6,72) | 8,0(*8,96) | 10,0(*11,20) | 12,0(*13,44) | 16,0(*17,92) | 20,0(*22,40) | 24,0 (*26,88) | 30,0 (*33,60) | 36.00 | 39.00 |
| Comprimento de Rosca b | 12.0 | 14.0 | 16.0 | 18.0 | 22.0 | 26.0 | 30.0 | 38.0 | 46.0 | 54.0 |
| Ø da Rosca d (máx) | 2.98 | 3.98 | 4.97 | 5.97 | 7.97 | 9.97 | 11.97 | 15.96 | 19.62 | 23.95 |
| Comprimento " L " | | | | | | | | | | |
| 8 | | | | | | | | | | |
| 10 | | | | | | | | | | |
| 12 | | | | | | | | | | |
| 16 | | | | | | | | | | |
| 20 | | | | | | | | | | |
| 25 | | | | | | | | | | |
| 30 | | | | | | | | | | |
| 35 | | | | | | | | | | |
| 40 | | | | | | | | | | |
| 50 | | | | | | | | | | |
| 60 | | | | | | | | | | |
| 70 | | | | | | | | | | |
| 80 | | | | | | | | | | |
| 90 | | | | | | | | | | |
| 100 | | | | | | | | | | |

Obs.: Abaixo da linha cheia, rosca parcial.

Material : Aço Inoxidável · Rosca Conforme DIN 13